Lidomont Pty Ltd Trading as **Prolube Lubricants** 15 Pinacle Street Brendale QLD 4500 | Ph: 07 3881 1733

 $\underline{sales@prolube.com.au} \ I \ \underline{www.prolube.com.au}$

ABN: 64 010 867 428

PRODUCT DATA SHEET

2 STROKE AIRCOOLED ENGINE OIL (AIR COOLED OPE - OUTDOOR POWER EQUIPMENT)

DESCRIPTION

2 Stroke Aircooled Engine oil is a semi synthetic lubricating oil blended for mixing with petrol for fuelling air-cooled 2 stroke motors. It has been formulated with high quality base stock and a special low ash additive pack to reduce build up on spark plugs and pistons.

Viscosity - Typical 9.7 cSt @ 100°C

APPLICATION

Designed for air-cooled 2 stroke motors in outdoor power equipment including lawn mowers, brush cutters, chain saw motors, motorcycles and air-cooled marine outboard motors. Mix with petrol fuel as per equipment manufacturers' recommendations.

It is not recommended for high performance water-cooled marine outboard motors (use Promarine TCW-3 Outboard Engine Oil).

STANDARDS

Meets or exceeds the following:

JASO: FA, FB, FC, FD

ISO-L-EGB, ISO-L-EGC, ISO-L-EGD

API: TC

Piaggio Hexagon

CONTAINER SIZES

Bulk, 1000 Litres IBC, 205 Litres, 20 Litres, 5 Litres, 1 Litres

Issue Date 1/9/2019



