

PRODUCT DATA SHEET

AGTRANS 410/430/450/460

(TRANSMISSION / HYDRAULIC FLUID)

DESCRIPTION

Agtrans 410, 430 450 and 460 are sophisticated transmission oils which have been developed to meet a range of transmissions used in agricultural and off-road equipment. They meet the requirements of the very latest Caterpillar TO-4, Allison C4, Komatsu and also Eaton and Dana manual transmissions. These oils provide excellent resistance to oxidation and friction and have desirable seal swell characteristics.

Grade	410	430	450	460
Viscosity (cSt @ 40°C Typ)	41	98	200	300
Viscosity (cSt @ 100°C)	6.4	11.6	18.7	24.1
SAE Viscosity	10	30	50	60

APPLICATION

Agtrans 410/430 are the primary recommendations for Allison C4 and Caterpillar powershift transmissions.

Agtrans 450/460 is the primary recommendation for most heavy-duty truck transmissions including Caterpillar, Fuller, Roadranger and Volvo.

STANDARDS

Meets performance requirements of major off-road transmission manufacturer including:

Caterpillar:	TO4 (TO-2 obsolete)
Allison:	C-4
Komatsu Dresser	KES 07.868.1
Eaton/Fuller	
ZF:	TE-ML03C TE-ML07F
Dana	Powershift
Eaton Vickers	35VQ-25 Vane Pump Test
Tremac TTC (SAE 50 only)	

CONTAINER SIZES

1000 Litres IBC, 205 Litres, 20 Litres

Issue Date 1/9/2019